

## PH PLUS CONTROL AGENT

**GRANULAR POOL CHEMICAL**  
STO 14175996-13-2008 with rev. 1-4



### USE:

Used to raise the pH level of swimming pool water.

### SPECIFICATIONS:

INDICATOR NAME	VALUE
Appearance and colour	white powder or granules
Active substance content, wt%, min.	80
Content of water-insoluble matter, wt%, max.	0.1
Iron content (Fe <sup>3+</sup> ), wt%, max.	0.008

Note: Caking may occur during storage and can be overcome by mixing.

### INSTRUCTIONS FOR USE:

The pH level below the recommended value should be raised to 7.2 by adding the pH plus control agent. To raise the pH by 0.1, add 100 g of the control agent to 10 m<sup>3</sup> of water. Dissolve the agent in the distribution tank of the dosing pump at a rate of 1 kg per 10 litres of water. If there is no distribution tank, pre-dissolve the product in a container and then pour the solution in portions close to the filtered water return nozzle or in several points, but not before filters. Deviations from the recommended dosage are possible for various hardness levels, therefore the water hardness must be tested after the product is added.

### PACKAGING:

Plastic buckets of 1 kg.

### TRANSPORTATION AND STORAGE:

Any means of transportation in accordance with the shipping rules applicable for the particular means of transportation. Store in a cool place, in a tightly sealed package. Keep away from acids and acid-containing products. Protect from moisture. Guaranteed shelf life is 2 years from the manufacture date.

### PRECAUTIONS:

Keep away from organics, acids and alkalis. Store only in the original package. Use rubber gloves and eye/face protection. Keep out of the reach of children. Do not mix with other chemicals. Protect from moisture. Thoroughly wash hands after handling. If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists or if you feel unwell, get medical attention.

### CONTACTS:

Phone: +7 (8442) 40-66-09, 40-66-11; fax: +7 (8442) 40-66-10; e-mail: ves@kaustik.ru